

Combi Drills / Hammers



These versatile tools are both a drill and a chipping hammer. A push of the rotation release button easily and quickly converts the tool to a hammer.

The CP 0009 and CP 0014RR rotary hammers are designed for a wide variety of construction and maintenance applications such as driving or setting masonry anchors and drilling holes in concrete, bricks or rock. As a hammer, these tools can be used for chipping, scarifying, scaling and cleaning welds.

All Models

- Excellent power-to-weight ratio helps drill holes faster and easier than comparable electric rotary hammers
- Built-in oiler provides continuous lubrication
- Teasing throttle for precise control
- Rotation release button converts tool to a hammer (except on CP 0009AC)
- Cushioned piston for smooth operation and long tool life
- Muffler available to reduce noise

CP 0009

- Right hand rotation
- With our SDS Plus Adaptor, can be used with electric hammer drill bits
- Spline version available
- Accepts all electric steel
- Adapter (R137586) round to SDS Plus

CP 0014

- Superior drilling rates
- Greater drilling capacity compared to plug hole drills
- Designed for production drilling of small holes



CP 0009

CP 0014

Drilling rates at 90 psi
in hard rock and concrete (use as guide only)

MODEL	Drill rate (in/min)	Hole diameter (in)
CP 0009	12	1¼
CP 0014 RR	18	1¼

Mufflers

MODEL	Part no.
CP 0009 A	F 815350
CP 0009 AC	F 826972
CP 0009 F	F 815350
CP 0014 RR	F 827044

MODEL	Part no.	Net weight (lb)	Air Inlet (in)	Overall length (in)	Impact rate (bpm)	Max Drilling Depth (in)	Type of chuck (in)	Chuck size (in)
CP 0009 —Air consumption at 90 psi: 19 cfm, 3/8" (NPT) air inlet thread								
CP 0009 A (with rotation release)	8900 0020 03	8.82	3/8 NPT	14¾	3420	17.5	round shank	3/4 x 3¾
CP 0009 AC*	8900 0020 08	8.82	3/8 NPT	14¾	3420	17.5	round shank	3/4 x 3¾
CP 0009 F (with rotation release)	8900 0020 04	8.82	3/8 NPT	14¾	3420	17.5	spline drive	
CP 0009 CS	8900 0020 07	8.82	3/8 NPT	14¾	3420	17.5	BSP collared head/hose	
CP 0014 RR —Air consumption at 90 psi: 47 cfm, 3/8" (NPT) air inlet thread								
CP 0014 RR	8900 0020 10	14.77	3/8 NPT	18½	2520	25.5	spring hex shank	7/8 x 3¾

* Use adapter (part number R 137586) in round shank units for SDS plus electric hammer drill bits.