

## DEWATERING PUMP SOLUTIONS



# Meet the CP0030

From clean water to abrasive sludge, Chicago Pneumatic's diaphragm pumps deliver when downtime isn't an option.

### Easy to Handle

It only takes one person to handle the CP0030

### Submersible

Thanks to the built-in non return valve. Add a silencer for lower noise levels

### Self Intake

Air intake with strainer prevents contaminants from entering pump

Safer Operations

### Self Priming

Reduces handling and downtime

### Lift more

Connect pumps in series to increase lifting capacity

Handles the Toughest Jobs

### Less stress

Pivoting connection pipe reduces hose strain

### Stable Operations

The strainer at the base prevents particles larger than 1-3/16" from passing through the pump

### Reach the Corners

Pivoting intake coupling & optional suction hose reach liquids in tight spaces



Model	CP0030	
Part number	8900004036	
Maximum head	194 ft	
Maximum flow	111 gpm	
Max. air requirements	72 cfm	
Weight	68 lbs	
Dimensions	15.4" x 13.0" x 23.0"	
Connection Thread	Fluid outlet	G 2 1/2"
	Air Inlet	G 3/4"

### About the CP0030

The CP0030 is a versatile pump built for tough jobs in construction, mining, and industrial applications. It's designed to handle the dirtiest, thickest, and most abrasive fluids with ease.

### Why Choose Pneumatic Pumps?

Choose pneumatic pumps for their safety and durability. They're spark-free and safe in wet or flammable environments, and their robust design handles contaminated fluids, high temperatures, and heavy-duty demands without the risk of overloading.